



GO! Project Idea Assembly Instructions

quilt





FABRIC REQUIREMENTS

- Fabric 1—1 yard
- Fabric 2—1½ yards
- Fabric 3—1½ yards (also for appliqué)
- Fabric 4—1½ yards (also for binding)
- Appliqué fabrics—scraps or fat quarters
- Fusible web product—1½ yards
- Backing-53" x 53"
- Batting-53" x 53"

GO! Dies used:

- GO! Circle-2", 3", 5" (55012)
- GO! Critters (55030)
- GO! Daisy (55327)
- GO! Fun Flower (55334)
- GO! Funky Flowers (55042)
- GO! Rose of Sharon (55045)
- GO! Round Flower (55007)

- · GO! Stems & Leaves (55331)
- GO! Strip Cutter-11/2" (55024)
- GO! Strip Cutter-21/2" (55014 or 55017)
- GO! Strip Cutter-41/2" (55054)
- GO! Tulip (55328)

CUTTING DIRECTIONS

Fabric 1:

Cut 1—33½" square

Fabric 2:

- Cut 2—4½" x 50" strips cut lengthwise
- Cut 2—2½" x 50" strips cut lengthwise

Fabric 3:

- Cut 2—4½" x 50" strips cut lengthwise
- Cut 2—2½" x 50" strips cut lengthwise

- Cut 4—2½" x 50" strips cut lengthwise for binding
- Cut 4—1½" x 50" strips cut lengthwise

Appliqué Fabrics:

Apply fusible web to the wrong side of selected fabrics following manufacturer's instructions.

Cut a variety of appliqué shapes using quilt diagram as inspiration.

SEWING DIRECTIONS

- 1. Remove paper backing from appliqué shapes.
- Reserve a few flying critters to appliqué after borders have been added.
- 3. Lay out shapes as desired on 33½" background fabric square on large pressing surface.
- 4. Fuse shapes in place following manufacturer's instructions.
- 5. Appliqué edges of shapes by hand or machine.
- 6. Layout and sew Fabric #2, 2½" strip; Fabric #4, 1½" strip; and Fabric #2, 4½" strip. Press toward Fabric #2 strips. Make two.





GO! Project Idea Assembly Instructions

quilt

- 7. Repeat for Fabric #3, 2½" strip; Fabric #4, 1½" strip; and Fabric #3, 4½" strip. Press toward Fabric #3 strips. Make two.
- 8. Pin and sew pieced border strips to background square matching centers. Start and stop stitching 1/4" from corners of background square.
- 9. From right side of quilt top, arrange border miter so seams of Fabric #4 match and corner lays flat. Press lightly.
- 10. Pin and sew each corner starting 1/4" from inner corner and following pressed crease. Press seams toward border. Trim excess border strip.
- 11. Add remaining appliqué shapes.

QUILTING & FINISHING

- 1. Layer batting between quilt top and backing.
- 2. Pin or baste layers together.
- 3. Model was machine quilted with an all-over design.
- 4. Add binding, mitering corners.